








Connection type:

0	1	2	3	4	5	6
Separate pocket with fixing screw	Fixed connection male thread	Union nut female thread	Union nut with double nipple	Union nut with additional thermowell acc. to DIN 16179 form CD oder DIN 43772 form 8	Turnable male thread	Movable clamp connection
						

Type:
Available stem Ø

	0 12/10	1 9/8	2 9/8	3 9/8	4 12/10	5 9/8	6 9/8
	Standard brass / Standard stainless steel						
4 mm	-	X	X	X	-	X	-
5 mm	-	X	X	X	-	X	-
6 mm	X	X	X	X	X	X	X
8 mm	X	X	X	X	X	X	X
10 mm	X	X	X	X	X	X	X
12 mm	X	X	X	X	X	X	X
13 mm	X	X	X	X	X	X	X
15 mm	X	X	X	X	X	X	X

Material varieties:

Brass 1.4305 1.4571

Available types of thread:

G

1/8 1/4 3/8 1/2 3/4 1

NPT

1/8 1/4 3/8 1/2 3/4 1

M

6 8 10 10x1 12x1 12x1,5 14x1
14x1,5 15x1 16x1 16x2 18x1,5 19x1 20x1
20x1,5 22x1 22x1,5 24x1 24x1,5 25x1 27x2

Further connections:

Hygienic coupling DN 25 / DN 50
Tapered thread and slotted ring nut DIN 11851 DN 25 / DN 50
Flange-thermowells for all requirements
e.g. DIN 2527 Form B / T / E
ND 6 / 10 / 16 / 25 / 40 / 64 / 100
NW 10 / 15 / 20 / 25 / 32

Other types on request!